Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-900-9405

Thread Class: 2b Thread Direction: Right-hand Body Style: Angle shape w/cable clamp Overall Diameter: 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type: Coupling facility
Thread Direction: Right-hand Body Style: Angle shape w/cable clamp Overall Diameter: 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Right-handBody Style:Angle shape w/cable clampOverall Diameter:2.718 inchesBody Angle In Deg:45.0Environmental Protection:Moisture resistant and salt water resistant and vibration resistantCable Entrance Diameter:1.625 inchesThreaded Device Type:
Body Style: Angle shape w/cable clamp Overall Diameter: 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Angle shape w/cable clamp Overall Diameter: 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Overall Diameter: 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
 2.718 inches Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Body Angle In Deg: 45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
45.0 Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Moisture resistant and salt water resistant and vibration resistant Cable Entrance Diameter: 1.625 inches Threaded Device Type:
Cable Entrance Diameter: 1.625 inches Threaded Device Type:
1.625 inches Threaded Device Type:
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40-62 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
30.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
6.856 inches
Distance From Centerline To Cable End:
3.325 inches

NSN 5935-00-900-9405

16

Un

N/a

No

Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi): **Thread Size:** 2.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 60 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.060 gold grains, troy and 0.060 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A039b0