

View Online at <https://aerobasegroup.com/nsn/5935-00-901-3887>

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.000 inches

Overall Width:

0.250 inches

Environmental Protection:

Humidity resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.750 inches

Board Accommodated Length:

1.400 inches single board

Board Accommodated Width:

0.100 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Terminals numbered 3, 7, and 11 solder coated

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.058 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.