

View Online at <https://aerobasegroup.com/nsn/5935-00-901-3995>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.109 inches

**Overall Height:**

1.781 inches

**Overall Width:**

1.781 inches

**Environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.437 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.437 inches

**Distance From Mounting Shoulder To Front Face:**

0.531 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

61-21 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

95.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0