

View Online at <https://aerobasegroup.com/nsn/5935-00-902-2930>

**Body Style:**

Straight shape, internal coupling w/backshell

**Overall Length:**

1.638 inches

**Overall Diameter:**

1.531 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-41 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

126.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

41 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.041 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-26482 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26482 spec.