# NSN 5935-00-902-2937

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-902-2937

view Online at https://aerobasegroup.com/nsn/5935-00-902-2937
Body Style:
Straight shape, external coupling
Overall Length:
1.709 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
Between 0.556 inches and 0.587 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
End Application:
Aircraft, f-16
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# NSN 5935-00-902-2937

Electrical Receptacle Connector - Page 2 of 2



# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:
---------------------------------

Feat

## **Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium and chromate

## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

## **Shell Material Specification:**

Qq-a-591 federal specification single material response

# **Included Contact Quantity:**

21 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

## **Special Features:**

Weapon system essential

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.021 gold grains, troy

## **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms3120 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.