## NSN 5935-00-902-3924

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-902-3924

**Body Style:** Right angle type **Overall Length:** 1.547 inches **Overall Width:** 0.437 inches **Body Height:** 0.312 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 all mating ends all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 600.0 all mating ends all contact groupings **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate mineral filled single mating end **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.010 gold grains, troy

## NSN 5935-00-902-3924

Electrical Receptacle Connector - Page 2 of 2



Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.

**Precious Material:**