NSN 5935-00-902-7073

Electrical Receptacle Connector - Page 1 of 2



Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.700 inches
Overall Height:
0.609 inches
Overall Width:
0.360 inches
Environmental Protection:
Moisture resistant
Distance Between Mounting Facility Centers:
1.400 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.250 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

NSN 5935-00-902-7073

Electrical Receptacle Connector - Page 2 of 2



Term	inal	Tvn	φ.
	·····	., ,	٠.

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Quality controlled for polaris

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.