Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-903-0042

### Thread Class:

2a and 2b and 2a

### **Thread Direction:**

Right-hand and right-hand and right-hand

### **Body Style:**

Straight shape

### **Overall Length:**

0.780 inches

#### **Overall Height:**

0.540 inches

### **Overall Width:**

0.190 inches

### **Distance Between Mounting Facility Centers:**

0.562 inches

### **Threaded Device Type:**

Coupling facility and mounting stud

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

7 single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

## Polarization Method:

Jackscrew

### **Connector Locking Method:**

Jackscrew-socket

### Thready Qty Per Inch (tpi):

32 and 32 and 40

### Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

## Insert Material Specification:

Mil-p-19833, ty gdi-30 military specification single material response single mating end



Included Contact Quantity:

7 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.007 gold grains, troy

### **Precious Material:**

Gold

## **Thread Series Designator:**

Unc and unc

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-p-19833 spec.