NSN 5935-00-903-3071

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-903-3071

| Za Za |
|---|
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.750 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.380 inches |
| Distance Between Mounting Facility Centers: |
| 0.562 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Thread Length: |
| 0.200 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Thread Size: |
| 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Included Contact Quantity: |
| 8 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Test Data Document: |
| 81349-mil-c-8384 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Unc

Thread Series Designator:

NSN 5935-00-903-3071

Electrical Receptacle Connector - Page 2 of 2



| Spec | cific | ation | Data: |
|------|-------|-------|-------|
|------|-------|-------|-------|

96906-ms24006-2 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0