Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-903-4801

Body Style:
Straight shape
Overall Length:
3.141 inches
Overall Height:
0.656 inches
Overall Width:
1.298 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.282 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
3600.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
5200.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy

## NSN 5935-00-903-4801

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Anodize

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0