NSN 5935-00-903-5066

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-903-5066

Body Style:

Straight shape

Overall Length:

Between 2.849 inches and 2.869 inches

Overall Height:

0.904 inches

Overall Width:

Between 0.725 inches and 0.745 inches

Unthreaded Mounting Hole Diameter:

Between 0.208 inches and 0.228 inches

Distance Between Mounting Facility Centers:

Between 2.521 inches and 2.541 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Insert Material Specification:

Mil-m-14, type sdg military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-00-903-5066

Electrical Receptacle Connector - Page 2 of 2



Special Features: Nylon dust cap included Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.050 gold grains, troy and 0.050 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):