Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-903-8422

·····
Body Style:
Straight shape
Overall Length:
4.469 inches
Overall Height:
0.422 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
4.063 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
725.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Contact Surface Treatment: Gold single mating end single contact grouping
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Aluminum alloy
Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

# NSN 5935-00-903-8422

Electrical Receptacle Connector - Page 2 of 2



Shell Guide Type And Location Designator:

L pin

#### Included Contact Quantity:

29 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

#### **Precious Material And Weight:**

0.029 gold grains, troy

#### **Precious Material:**

Gold

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.