NSN 5935-00-904-1061

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-904-1061

9. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
Body Style:
Straight shape, external coupling
Overall Length:
0.978 inches
Overall Height:
0.828 inches
Overall Width:
0.828 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.462 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
40393 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
60.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shall Material

NSN 5935-00-904-1061 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
ncluded Contact Quantity:
3 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3112 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0