NSN 5935-00-904-2872



| Electrical Receptacle Connector - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-00-904-2872 |
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.062 inches |
| Overall Height: |
| 0.531 inches |
| Overall Width: |
| 0.250 inches |
| Distance Between Mounting Facility Centers: |
| 0.814 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 1850.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 2590.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment |

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Plastic diallyl phthalate

Shell Material Specification:

Mil-m-14, ty sdg-f military specification single material response

NSN 5935-00-904-2872

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.