

View Online at <https://aerobasegroup.com/nsn/5935-00-904-4050>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

1.400 inches

Overall Height:

1.300 inches

Overall Width:

0.781 inches

Environmental Protection:

Salt water resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 2nd mating end all contact groupings

End Application:

Mrap - m-atv w/cs13 pop and sne

Thread Size:

0.625 inches and 0.625 inches

Contact Material:

Copper alloy 2nd mating end 2nd contact grouping

Contact Surface Treatment:

Gold all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-533, comp ht federal specification single material response all mating ends single contact grouping and qq-b-330, comp a federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-613, comp 11 federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 1st mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-prf-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349 - mil-prf-55339/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.