

View Online at <https://aerobasegroup.com/nsn/5935-00-904-7720>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

0.870 inches

Overall Height:

1.430 inches

Overall Width:

0.330 inches

Environmental Protection:

Vibration resistant

Cable Entrance Diameter:

Between 0.240 inches and 0.360 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

14 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

56 and 56

Thread Size:

0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.