Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-904-9231

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches |
| Overall Height: |
| 1.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.562 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16 single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 3200.0 single mating end 2nd contact grouping |
| Polarization Method: |
| Shell |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Spring friction |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| |



Terminal Type: Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Guide Type And Location Designator: B pin **Included Contact Quantity:** 9 single mating end 3rd contact grouping Included Contact Type: Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.016 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0