

View Online at <https://aerobasegroup.com/nsn/5935-00-904-9855>

Body Style:

Straight shape, external coupling strain relief

Overall Height:

1.343 inches

Overall Width:

1.343 inches

Body Length:

Between 1.625 inches and 2.140 inches

Environmental Protection:

Heat resistant and salt water resistant and vibration resistant and watertight

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

Cable Entrance Diameter:

0.531 inches

Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

31 number 20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

95.0 and 145.0 and 220.0 and 255.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

31 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms24264 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.