Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-905-1016

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

1.109 inches

# **Overall Height:**

1.188 inches

## **Overall Width:**

1.188 inches

### **Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

## **Unthreaded Mounting Hole Diameter:**

## 0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

#### Distance ве

0.906 inches

# Distance From Mounting Shoulder To Front Face:

0.531 inches

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

197p single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

40.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## Insert Position In Deg:

0.0

## Shell Type:

Solid

# **Connector Locking Method:**

Spring friction

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# Insert Material:

Rubber synthetic single mating end



## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd

treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

## **Shell Material:**

Aluminum alloy

#### Shell Surface Treatment:

Chromate zinc

#### **Included Contact Quantity:**

7 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.007 gold grains, troy and 0.007 silver grains, troy

## **Precious Material:**

Gold and silver

Shelf Life:

N/a

# Unit Of Measure:

Demilitarization:

No

--

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.