

View Online at <https://aerobasegroup.com/nsn/5935-00-905-1078>

Thread Class:

2a

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.147 inches and 1.167 inches

Overall Height:

Between 1.115 inches and 1.135 inches

Overall Width:

Between 2.302 inches and 2.322 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.745 inches and 0.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.057 inches and 2.067 inches

Distance From Mounting Shoulder To Front Face:

Between 0.334 inches and 0.354 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

8 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

23.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

8 single mating end single contact grouping

Special Features:

Float mounted shoulder screws

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0