NSN 5935-00-905-1087

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-905-1087 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 0.882 inches and 0.922 inches **Overall Height: 3.298** inches **Overall Width:** 1.694 inches **Environmental Protection:** Vibration resistant and shock resistant and moisture resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 2.981 inches and 2.991 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.495 inches and 0.505 inches **Distance From Mounting Shoulder To Front Face:** Between 0.636 inches and 0.676 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 66 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 40

Thread Size:

0.112 inches

NSN 5935-00-905-1087

Electrical Receptacle Connector - Page 2 of 3



T	ermi	nal	I oc	atior	١:
	CITT	ı ıaı		alivi	• •

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end

Shell Guide Type And Location Designator:

C slot

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

66 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.066 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5935-00-905-1087

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.