

View Online at <https://aerobasegroup.com/nsn/5935-00-905-5276>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape

**Overall Length:**

1.656 inches

**Overall Height:**

3.041 inches

**Overall Width:**

1.582 inches

**Cable Entrance Diameter:**

0.370 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

20.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

275.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Conduit nut

**Thread Size:**

0.719 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 4 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Test Data Document:**

10001-2159406 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.