

View Online at <https://aerobasegroup.com/nsn/5935-00-906-3182>

Body Style:

Straight shape

Overall Length:

Between 1.158 inches and 1.248 inches

Overall Height:

Between 3.095 inches and 3.125 inches

Overall Width:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.432 inches and 1.442 inches

Distance From Mounting Shoulder To Front Face:

Between 0.751 inches and 0.781 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

45 1st mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 2nd mating end 2nd contact grouping

Polarization Method:

2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic melamine all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Solder well all mating ends all contact groupings

Shell Material:

Aluminum alloy a380.0

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type mme military specification single material response all mating ends

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.070 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.