NSN 5935-00-908-0094

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-908-0094 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 2.100 inches **Body Width:** 0.360 inches **Body Height:** 0.360 inches **Environmental Protection:** Shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 1.800 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.112 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-00-908-0094

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.015 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.015 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0