Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-908-6870

a
hread Direction:
light-hand
overall Length:
.990 inches
overall Height:
.000 inches
overall Width:
.000 inches
nvironmental Protection:
loisture resistant
Inthreaded Mounting Hole Diameter:
.142 inches
center To Center Distance Between Mounting Facilities Parallel To Height:
.562 inches
istance Between Centerlines Of Mounting Facilities Parallel To Body Width
.562 inches
hreaded Device Type:
Coupling facility
lating End Quantity:
contact Removability:
lonremovable single mating end single contact grouping
contact Maximum Current Rating In Amps:
2.0 single mating end single contact grouping
contact Maximum Ac Voltage Rating In Volts:
00.0 single mating end single contact grouping
contact Maximum Dc Voltage Rating In Volts:
00.0 single mating end single contact grouping
connector Locking Method:
xternally threaded shell
hready Qty Per Inch (tpi):
8
° hread Size:
750 inches
nsert Material:
ubber single mating end
hell Material:
luminum alloy
hell Surface Treatment:

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 

37 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Thread Series Designator:**

Uns

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0