Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-909-1273

| view online at https://defobalegroup.com/hai//0000 00 000 1210 |
|--|
| Body Style: |
| Multiple card type |
| Overall Length: |
| 1.843 inches |
| Overall Height: |
| 0.656 inches |
| Overall Width: |
| 0.328 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Distance Between Mounting Facility Centers: |
| 1.531 inches |
| Board Accommodated Length: |
| 1.078 inches single board |
| Board Accommodated Width: |
| Between 0.054 inches and 0.071 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of independent contacts inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-19833, ty gdi-30 military specification single material response single mating end |
| Included Contact Type: |
| Bifurcated spring single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material: |
| Gold |

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.