

View Online at <https://aerobasegroup.com/nsn/5935-00-910-5021>

Body Style:

Straight shape

Overall Length:

1.157 inches

Overall Height:

1.125 inches

Overall Width:

2.312 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.062 inches

Distance From Mounting Shoulder To Front Face:

0.782 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

57 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

7.5 all mating ends single contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Solid

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response all mating ends single contact grouping

Guide Design And Location:

Hexagon shape female post left-hand at 7 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Type:

Round socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.114 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.