Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-910-5854

Body Style:

Straight shape, flush mount

Overall Length:

Between 2.489 inches and 2.539 inches

Overall Height:

Between 3.095 inches and 3.125 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Moisture resistant and salt water resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

Between 0.751 inches and 0.781 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

40c1 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 2nd mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

583.0 2nd mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

824.0 2nd mating end all contact groupings

Shell Type:

Split

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 cl 4 military specification single treatment response 2nd mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings



Shell Material:	
Aluminum alloy a380.0	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification single treatment response	;
Shell Material Specification:	
Qq-a-591, alloy a380 federal specification single material response	
Insert Material Specification:	
Mil-m-14 ty sdi-5 military specification single material response single	mating end
Precious Material And Location:	
Contact surfaces gold and contact surfaces silver	
Precious Material And Weight:	
0.040 gold grains, troy and 0.040 silver grains, troy	
Precious Material:	
Gold and silver	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	