

View Online at <https://aerobasegroup.com/nsn/5935-00-910-9304>

Thread Class:

Za

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.734 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Shock proof and vibration proof

Distance From Mounting Shoulder To Front Face:

0.422 inches

Mounting Facility Thickness:

0.203 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Smp single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.