Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-911-5893

Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
3.300 inches
Overall Height:
1.111 inches
Overall Width:
0.700 inches
Distance Between Mounting Facility Centers:
2.800 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.300 inches
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-19833 ty gdi-30 military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping

NSN 5935-00-911-5893

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surfaces silver **Precious Material And Weight:** 0.023 gold grains, troy and 0.023 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.