NSN 5935-00-912-5926

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-912-5926

| view Online at https://aerobasegroup.com/nsr/5935-00-91z-5926 |
|--|
| Body Style: |
| Straight shape, internal coupling w/backshell |
| Overall Length: |
| 1.203 inches |
| Overall Diameter: |
| 1.484 inches |
| Environmental Protection: |
| Salt water resistant and moisture resistant and vibration resistant and corrosion resistant and humidity resistant and shock proof |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 37-2p single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 25.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Ball |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |

Included Contact Quantity:

24 single mating end single contact grouping

NSN 5935-00-912-5926

Electrical Plug Connector - Page 2 of 2



| Included Contact Type: |
|------------------------|
|------------------------|

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.024 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0