NSN 5935-00-912-6513

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-912-6513 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.547 inches **Bushing Diameter:** 0.234 inches Diameter: 0.312 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 3p single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction Thread Length: 0.188 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic melamine single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-912-6513

Electrical Receptacle Connector - Page 2 of 2



| 1: |
|----|
| |

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

3 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.