## NSN 5935-00-912-8979

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-912-8979 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** Between 4.332 inches and 4.352 inches **Overall Width:** 0.770 inches **Body Height:** 0.469 inches **Unthreaded Mounting Hole Diameter:** 0.138 inches **Distance Between Mounting Facility Centers:** 3.968 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Length:** 0.270 inches **Thread Size:** 0.138 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** 

Pin single mating end 2nd contact grouping

## NSN 5935-00-912-8979

Electrical Receptacle Connector - Page 2 of 2



## Insert Material Specification: Mil-m-19833, type gdi-30 military specification single material response single mating end Included Contact Quantity: 28 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Four mounting studs Precious Material And Location: Contact and guie surfaces gold Precious Material And Weight: 0.028 gold grains, troy Precious Material:

Shelf Life:

Sileii Liie.

N/a

Unc

Gold

**Unit Of Measure:** 

**Thread Series Designator:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.