Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-912-8979

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
Between 4.332 inches and 4.352 inches
Overall Width:
0.770 inches
Body Height:
0.469 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
3.968 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.270 inches
Thread Size:
0.138 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end 2nd contact grouping

## NSN 5935-00-912-8979

Electrical Receptacle Connector - Page 2 of 2



Insert Materia	I Specification:
Mil-m-19833, t	ype gdi-30 military specification single material response single mating end
Included Con	tact Quantity:
28 single matir	ng end single contact grouping
Included Con	tact Type:
Round pin sing	gle mating end single contact grouping
Special Featu	res:
Four mounting	studs
Precious Mate	erial And Location:
Contact and g	uie surfaces gold
Precious Mate	erial And Weight:
0.028 gold gra	ins, troy
Precious Mate	erial:
Gold	
Thread Series	B Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measu	ıre:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (milita	ry Standard):
Mil-m-19833 s	Dec.