NSN 5935-00-912-9634

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-912-9634

| Body Style: |
|--|
| Straight shape, internal coupling |
| Overall Length: |
| 0.965 inches |
| Overall Diameter: |
| 0.445 inches |
| Cable Entrance Diameter: |
| 0.150 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bnc single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 120.0 and 240.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet slot |
| Connector Cable Strain Relief Method: |
| Compression nut |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Gold |
| Included Contact Quantity: |

Included Contact Type:

Coaxial socket single mating end single contact grouping

1 single mating end single contact grouping

NSN 5935-00-912-9634Electrical Plug Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact and body surfaces gold |
| Precious Material And Weight: |
| 0.105 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0