## NSN 5935-00-913-0808

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-913-0808

#### **Body Length:**

Between 1.235 inches and 1.297 inches

**Overall Diameter:** 

0.938 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

#### **Mating End Quantity:**

1

#### **Contact Position Arrangement Style:**

7-oct single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

#### **Shell Type:**

Solid

## **Connector Locking Method:**

Spring friction

#### **Connector Cable Strain Relief Method:**

Cable clamp

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## Terminal Type:

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

#### **Included Contact Quantity:**

7 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

 $0.035 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.035 \ \text{silver grains}, \ \text{troy}$ 

# NSN 5935-00-913-0808

Electrical Plug Connector - Page 2 of 2



P	reci	nus	Materia	ŀ

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0