

View Online at <https://aerobasegroup.com/nsn/5935-00-913-7549>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Chassis type

Overall Height:

1.125 inches

Unthreaded Mounting Hole Diameter:

0.164 inches

Distance Between Mounting Facility Centers:

1.750 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

Thread Size:

0.164 inches

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Screw single mating end all contact groupings

Insert Material Specification:

Mil-m-14, type cfg military specification single material response single mating end

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

U-socket single mating end 2nd contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.