

View Online at <https://aerobasegroup.com/nsn/5935-00-913-7549>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Chassis type

**Overall Height:**

1.125 inches

**Unthreaded Mounting Hole Diameter:**

0.164 inches

**Distance Between Mounting Facility Centers:**

1.750 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Connector Locking Method:**

Contact twistlock

**Thread Size:**

0.164 inches

**Terminal Location:**

Side single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Screw single mating end all contact groupings

**Insert Material Specification:**

Mil-m-14, type cfg military specification single material response single mating end

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

U-socket single mating end 2nd contact grouping

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.