

View Online at <https://aerobasegroup.com/nsn/5935-00-913-9010>

**Body Style:**

Straight edge type w/card guide

**Overall Length:**

4.206 inches

**Overall Height:**

Between 0.818 inches and 0.838 inches

**Overall Width:**

Between 0.521 inches and 0.541 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.118 inches and 0.138 inches

**Distance Between Mounting Facility Centers:**

Between 3.919 inches and 3.949 inches

**Board Accommodated Length:**

3.715 inches all boards

**Board Accommodated Width:**

Between 0.153 inches and 0.173 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a, hard federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

35 single mating end single contact grouping

**Included Contact Type:**

Spring pincers single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.035 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.