NSN 5935-00-913-9311

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-913-9311 **Overall Length:** 3.970 inches **Overall Height:** 1.000 inches Overall Width: Between 0.830 inches and 0.838 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** Between 3.622 inches and 3.628 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 750.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Lever-pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Nickel

Included Contact Quantity:

32 single mating end single contact grouping

NSN 5935-00-913-9311

Electrical Receptacle Connector - Page 2 of 2



			-1-	٠.	<u> </u>		-4	Tvi	
ı	IIC	ıu	ue	u	υU	III	Cι	1 7 1	JE.

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0