Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-914-0922

Overall Length:3.484 inchesOverall Height:0.691 inchesOverall Width:Between 0.394 inches and 0.404 inchesEnvironmental Protection:Heat resistant and pressure proof and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.157 inchesBoard Accommodated Length:3.057 inches single board and 3.067 inches single board
Overall Height:0.691 inchesOverall Width:Between 0.394 inches and 0.404 inchesEnvironmental Protection:Heat resistant and pressure proof and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.157 inchesBoard Accommodated Length:3.057 inches single board and 3.067 inches single board
0.691 inches Overall Width: Between 0.394 inches and 0.404 inches Environmental Protection: Heat resistant and pressure proof and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Overall Width: Between 0.394 inches and 0.404 inches Environmental Protection: Heat resistant and pressure proof and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Between 0.394 inches and 0.404 inches Environmental Protection: Heat resistant and pressure proof and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Environmental Protection: Heat resistant and pressure proof and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Heat resistant and pressure proof and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Unthreaded Mounting Hole Diameter: 0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
0.157 inches Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
Board Accommodated Length: 3.057 inches single board and 3.067 inches single board
3.057 inches single board and 3.067 inches single board
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Spring pincers single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.