## NSN 5935-00-914-1466

**Thread Class:** 

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-914-1466

| Thread Direction:                                    |
|--|
| Right-hand   |
| Body Style:  |
| Straight shape, internal coupling                    |
| Overall Length:                                      |
| 3.188 inches   |
| Overall Diameter:                                    |
| 1.969 inches   |
| Threaded Device Type:                                |
| Coupling facility                                    |
| Mating End Quantity:                                 |
| 1  |
| Contact Position Arrangement Style:                  |
| 28-11 single mating end                              |
| Contact Removability:                                |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps:              |
| 41.0 single mating end 1st contact grouping          |
| Contact Maximum Ac Voltage Rating In Volts:          |
| 500.0 single mating end all contact groupings        |
| Contact Maximum Dc Voltage Rating In Volts:          |
| 700.0 single mating end all contact groupings        |
| Polarization Method:                                 |
| Keyway or multiple keyway                            |
| Insert Position In Deg:                              |
| 0.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:                            |
| Internally threaded coupling nut                     |
| Thready Qty Per Inch (tpi):                          |
| 18   |
| Thread Size:   |
| 1.750 inches   |
| Terminal Location:                                   |
| Back single mating end all contact groupings         |
| Contact Material:                                    |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment:                           |
| Gold single mating end all contact groupings         |

## **NSN 5935-00-914-1466**Electrical Plug Connector - Page 2 of 2



| insert Materiai:                                     |
|--|
| Plastic single mating end                            |
| Terminal Type:                                       |
| Solder well single mating end all contact groupings  |
| Shell Material:                                      |
| Aluminum alloy                                       |
| Shell Surface Treatment:                             |
| Anodize  |
| Included Contact Quantity:                           |
| 4 single mating end 1st contact grouping             |
| Included Contact Type:                               |
| Round socket single mating end all contact groupings |
| Precious Material And Location:                      |
| Contact surfaces gold                                |
| Precious Material And Weight:                        |
| 0.022 gold grains, troy                              |
| Precious Material:                                   |
| Gold   |
| Thread Series Designator:                            |
| Uns  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A039b0   |
|  |