NSN 5935-00-914-2208

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-914-2208 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.006 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.812 inches **Overall Height:** 0.053 inches **Overall Width:** 0.720 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:**

Plastic phenolic single mating end

NSN 5935-00-914-2208

Electrical Receptacle Connector - Page 2 of 2



Terminal	Type:
----------	-------

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833 ty gd1-30 military specification single material response single mating end

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.075 gold grains, troy and 0.075 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.