

View Online at <https://aerobasegroup.com/nsn/5935-00-914-7483>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 0.734 inches and 0.766 inches

**Overall Diameter:**

0.312 inches

**Cable Entrance Diameter:**

0.105 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded coupling ring

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-14548 military specification 1st treatment response single mating end single contact grouping and mil-f-14072, finish -351 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, h federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Mil-f-14072, finish -351 military specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact and body surfaces silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.105 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-14548 spec.