Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-914-9273

| View Online at https://aerobasegroup.com/nsn/5935-00-914-9273   |
|---|
| Thread Class:   |
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight edge type w/mounting flange                            |
| Overall Length:   |
| 3.719 inches  |
| Overall Height:   |
| 0.406 inches  |
| Overall Width:  |
| 0.328 inches  |
| Environmental Protection:                                       |
| Corrosion resistant   |
| Distance Between Mounting Facility Centers:                     |
| 3.406 inches  |
| Board Accommodated Length:                                      |
| 2.960 inches single board                                       |
| Threaded Device Type:   |
| Mounting hole   |
| Board Accommodated Width:                                       |
| 0.062 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                             |
| 2 rows of independent contacts inserted board single mating end |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping          |
| Contact Maximum Current Rating In Amps:                         |
| 7.5 single mating end single contact grouping                   |
| Polarization Method:  |
| Fixed contact to contact  |
| Connector Locking Method:                                       |
| Friction  |
| Thready Qty Per Inch (tpi):                                     |
| 40  |
| Thread Size:  |
| 0.112 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping                  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping          |



| Gold single   | mating end single contact grouping  |
|---------------|---|
| Insert Mate   |   |
| Plastic diall | yl phthalate single mating end and glass fiber single mating end                            |
| Contact Su    | Irface Treatment Specification:   |
| Mil-g-45204   | I military specification single treatment response single mating end single contact groupin |
| Terminal T    | ype:  |
| Tab, solder   | r lug single mating end single contact grouping   |
| Insert Mate   | erial Specification:  |
| Mil-m-1983    | 3, type gdi-30 military specification all material responses single mating end              |
| Included C    | ontact Quantity:  |
| 36 single m   | ating end single contact grouping   |
| Included C    | ontact Type:  |
| Bifurcated s  | spring single mating end single contact grouping  |
| Precious N    | laterial And Location:  |
| Contact sur   | faces gold  |
| Precious N    | laterial And Weight:  |
| 0.036 gold (  | grains, troy  |
| Precious N    | laterial:   |
| Gold          |   |
| Thread Ser    | ies Designator:   |
| Unc           |   |
| Shelf Life:   |   |
| N/a           |   |
| Unit Of Me    | asure:  |
|               |   |
| Demilitariz   | ation:  |
| No            |   |
| Fiig:         |   |
| A039b0        |   |
| Mil-std (mi   | litary Standard):   |
| Mil-g-45204   | l spec.   |