

View Online at <https://aerobasegroup.com/nsn/5935-00-915-3410>

Body Style:

Straight shape

Overall Length:

5.090 inches

Overall Height:

0.670 inches

Overall Width:

0.438 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.144 inches

Distance Between Mounting Facility Centers:

4.684 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Mating end and shell

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-19833 ty gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

X slot

Included Contact Quantity:

23 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.023 gold grains, troy and 0.023 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.