Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-916-0319

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling Overall Length:
1.531 inches
Overall Height:
2.000 inches Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
Between 0.145 inches and 0.151 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.557 inches and 1.567 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.557 inches and 1.567 inches
Distance From Mounting Shoulder To Front Face:
Between 0.812 inches and 0.822 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-16 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell



**Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.020 gold grains, troy and 0.020 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0