

View Online at <https://aerobasegroup.com/nsn/5935-00-917-1547>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle shape w/backshell

Overall Length:

1.014 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.495 inches and 0.502 inches

Overall Height:

1.547 inches

Overall Width:

Between 0.684 inches and 0.697 inches

Environmental Protection:

Weatherproof

Unthreaded Mounting Hole Diameter:

Between 0.136 inches and 0.144 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.495 inches and 0.502 inches

Distance From Mounting Shoulder To Rear Face:

0.859 inches

Flange Length:

Between 0.684 inches and 0.697 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 260.0 degrees fahrenheit

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, 1/2 hard federal specification single material response

Insert Material Specification:

Mil-p-19465 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact and body surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19465 spec.