

View Online at https://aerobasegroup.com/nsn/5935-00-917-3352

### Thread Class:

2a and 2b and 2a

### **Thread Direction:**

Right-hand and right-hand and right-hand

### **Body Style:**

Rectangular shape

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

#### **Overall Height:**

0.656 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

# Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

### **Polarization Method:**

Jackscrew and shell

Shell Type:

Solid

#### **Connector Locking Method:**

Jackscrew-socket

#### Thready Qty Per Inch (tpi):

32 and 32 and 40

#### Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Criticality Code Justification:**

Feat

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Anodize

# Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

## Unable To Decode:

Unable to decode and unable to decode

### **Special Features:**

Shell polarized at position c



## **Thread Series Designator:**

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-m-14 spec.