

View Online at <https://aerobasegroup.com/nsn/5935-00-917-3453>

Body Style:

Straight shape, pc type

Overall Length:

4.285 inches

Overall Height:

0.708 inches

Overall Width:

0.340 inches

Environmental Protection:

Shock resistant and vibration resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

4.031 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Connector Locking Method:

Spring friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Color:

Black

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.